



## ENCLOSED SWITCH-DISCONNECTORS

20÷80A

2P-3P-3P+N-4P



20÷40A

2P-3P-3P+N-4P



63÷80A

2P-3P-3P+N-4P



### InfoTECH

ITALY

WORLDWIDE


Numero Verde





800-018009

ScameOnLine

www.scame.com

infotech@scame.com

		20÷40A 2P-3P-3P+N-4P	63÷80A 2P-3P-3P+N-4P
Wire range		1.5÷10mm <sup>2</sup>	10-35mm <sup>2</sup>
Tightening torque	Terminal screws	0.8Nm	3.6Nm
	Fixing screws	1.2Nm	1.2Nm
Wire strip length		10mm	13mm








 **ATTENTION**

When mounting or removing additional elements the switch **has to be in OFF position** for avoiding damages to mechanism.







When removing main switch following instruction for avoiding damages.

## THERMOPLASTIC ENCLOSURES

**20÷40A**  
**2P-3P-3P+N-4P**






**63-80A**  
**2P-3P-3P+N-4P**




## ALUMINIUM ENCLOSURES

**20÷40A**  
**2P-3P-3P+N-4P**





Bottom side

1xM20+1xM25  
Open threaded  
cable entry  
with cap






Top side

1xM20+1xM25  
Open threaded  
cable entry  
with cap




**63-80A**  
**2P-3P-3P+N-4P**



Bottom side

2xM32  
Open threaded  
cable entry  
with cap



Top side

2xM32  
Open threaded  
cable entry  
with cap

