


# CPST1.5/3



1.5 mm<sup>2</sup> 3-wire connector for sensor and actuator.

Sensor and Actuator Push in Terminal Block are ideal for wiring modern machine control systems. These are extremely compact and space saving.

### TECHNICAL DATA

Rated Voltage	250 V
Rated Current	13.5 A
Housing Material	Polyimide
Standard Colour	Grey
Product Function	Select
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	4 KV
Pollution Degree	3

### CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	1.5 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	14 mm <sup>2</sup>
Stripping Length	8 mm

### DIMENSIONS

Height with DIN 32 rail	mm
Height with DIN 35 x 15 mm rail	55.55 mm
Height with DIN 35 x 7.5 mm rail	48.1 mm
Length	79.8 mm
Width (Thickness)	3.5 mm

### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPST1.5/3	1.5 sq.mm Sensor and actuator push in Terminal Block in Grey colour	50
CPST1.5/3L6-60V	1.5 sq.mm Sensor and actuator push in Terminal Block in Grey colour	50
CPST1.5/3L110-240V	1.5 sq.mm Sensor and actuator push in Terminal Block in Grey colour	50

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	MS3.5	Marking Tag Blank suitable for 3.5mm Terminal Blocks	100
	JX1.5/2	Shorting Link for 1.5 sq mm series	100
	JX1.5/3	Shorting Link for 1.5 sq mm series	50
	JX1.5/4	Shorting Link for 1.5 sq mm series	50
	JX1.5/10	Shorting Link for 1.5 sq mm series	10
	EPCPPT2.5/3	End Plate for CPST and CPPT	50
	MC3.5	MARKER CARD 3MM PITCH WITH 90 TAGS	10


### APPROVALS



### NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CPST1.5/3



**connectwell**  
THE RIGHT CONNECTION

**RATINGS AS PER STANDARDS**

<b>STANDARDS</b>	<b>UL 1059</b>	<b>CSA C.22.2 No:158</b>	<b>IEC/EN60947-7-1</b>
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	14 AWG	14 AWG	1.5 mm <sup>2</sup>
Rated Voltage	150 V	150 V	250 V
Rated Current	15 A	15 A	13.5 A